
30
32
40
36
Clock Divider
Modulator AIP
Mod Event Table (1K x 48)
Mod Sequence RAM (1K x 32)
Modulator
DAC
DAC
I
Q
digital I
digital Q
I sample
Q sample
Demod Event Table (1K x 48)
Demod Sequence RAM (1K x 32)
Demodulator
Loopback data for debugging
I sample from external ADC
Q sample from external ADC
ADC
ADC
analog I
analog Q
Demodulator AIP
140
38
Clock Divider
Configuration Bus
Feature Pins
general-purpose digital outputs
Processor Interface
Pulse Width Modulators
PWM outputs
PowerPC Bus
Utopia TX/RX

Figure 1


32
44
Event Handler
46
Frame Formatter
Micro-Sequencer
50
Modulator Air Interface Processor
40
44
Event Handler
46
Micro-Sequencer
Frame Deformatter
52
Demodulator Air Interface Processor
42
Air Interface Processor

Figure 2

Instruction	47	46	45	44	43	42	41	40	39	38	37	36	35	34	33	32	31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
Type 1	0	0	ALU opcode					S	W	Rd				Rn				operand 2											branch code								pass address												fail address												
Type 2	0	1	0	0	Rhi				-				Rlo					32-bit data																																		
Type 3	0	1	0	1	Rhi				Imm_lo									32-bit data																																		
Type 4	0	1	1	0	Rhi				-				Rlo					-																															Rd					
Type 5	0	1	1	1	Rhi				Imm_lo									-																															Rd					
Type 6	1	T	D	Q				0	Microsequencer address									trigger time																																				
Type 7	1	-			0	1	-	burst info																																												
Type 8	1	-	A	1	1	-	mask																																												

Instruction Type 1: ALU Operations
Instruction Type 2: Write register
Instruction Type 3: Write register immediate
Instruction Type 4: Read register
Instruction Type 5: Read register immediate
Instruction Type 6: Trigger
Instruction Type 7: BURST
Instruction Type 8: WAIT
[A='0' → until any of (R12 and mask) bits are set]
[A='1' → until all of (R12 and mask) bits are set]

Figure 3: Event Handler Instruction Set Summary



Instruction	47	46	45	44	43	42	41	40	39	38	37	36	35	34	33	32	31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
Type 2	0	1	0	0	Rhi				-	-	-	-	Rlo		32-bit data																																	
Type 3	0	1	0	1	Rhi				Imm_lo						32-bit data																																	
Type 4	0	1	1	0	Rhi				-	-	-	-	Rlo		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	Rd			
Type 5	0	1	1	1	Rhi				Imm_lo						-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	Rd			

Figure 4: Register Access Instructions



Instruction	47	46	45	44	43	42	41	40	39	38	37	36	35	34	33	32	31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
Type 6	1	T	D	Q	0	Microsequencer address																																												
															trigger time																																				

Figure 5: Data Scheduling Instructions



Instruction	47	46	45	44	43	42	41	40	39	38	37	36	35	34	33	32	31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
Type 7	1	-			0	1	-	burst info																																											

Figure 6: Burst Descriptor Instruction



33	32	31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
PS	value to DDS/Fractional-N counter																																

Figure 7: Modulator Burst Info Field Format



33	32	31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
User ID																PS	Expected Length																	

Figure 8: Demodulator Burst Info Field Format



Instruction	47	46	45	44	43	42	41	40	39	38	37	36	35	34	33	32	31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
Type 8	1	-	A	1	1	-	mask																																										

Figure 9: Processor Wait Instruction

opcode	name	Description
00000	JZ	Jump to Zero
00001	CJS	Conditional Jump to Subroutine
00010	JMAP	Jump Map
00011	CJP	Conditional Jump Pipeline
00100	PUSH	Push/Conditional Load Counter
00101	JSRP	Conditional Jump to Subroutine
00110	CJV	Conditional Jump Vector
00111	JRP	Conditional Jump
01000	RFCT	Repeat Loop Counter Not Equal to Zero
01001	RPCT	Repeat Pipeline Counter Not Equal to Zero
01010	CRTN	Conditional Return
01011	CJPP	Conditional Jump Pipeline and Pop
01100	LDCT	Load Counter and Continue
01101	LOOP	Test End of Loop
01110	CONT	Continue
01111	TWB	Three Way Branch
10000	FORK	Multiway Branch
others		reserved

Figure 10: Microsequencer Instruction Set



Figure 11: Microsequencer memory format



Figure 12: Configuration of condition codes and fork

1	x	x	1	x	Match	
0	0	0	0	0	0	0
0	0	0	0	1	0	
0	0	0	1	0	0	
0	0	0	1	1	0	
0	0	1	0	0	0	0
0	0	1	0	1	0	
0	0	1	1	0	0	
0	0	1	1	1	0	
0	1	0	0	0	0	0
0	1	0	0	1	0	
0	1	0	1	0	0	
0	1	0	1	1	0	
0	1	1	0	0	0	0
0	1	1	0	1	0	
0	1	1	1	0	0	
0	1	1	1	1	0	
1	0	0	0	0	0	C
1	0	0	0	1	0	
1	0	0	1	0	1	
1	0	0	1	1	1	
1	0	1	0	0	0	C
1	0	1	0	1	0	
1	0	1	1	0	1	
1	0	1	1	1	1	
1	1	0	0	0	0	C
1	1	0	0	1	0	
1	1	0	1	0	1	
1	1	0	1	1	1	
1	1	1	0	0	0	C
1	1	1	0	1	0	
1	1	1	1	0	1	
1	1	1	1	1	1	

Figure 13



Figure 14

Event Handler

44

Time	Sequence
T=200	TS
T=400	TS
T=600	BOD

Figure 15

Microsequencer

46

Sequence	Actions
TS	send header send 1 ATM cell add RS encoding
BOD	send header send 3 ATM cells add RS encoding

68

70

Figure 16

Terminal Modulator Block Diagram



Fig 17



Fig 18



Figure 19



Figure 20



Figure 21

Terminal Demodulator Block Diagram



Fig 22



Fig 23